



## ***AISIN Fully Synthetic ATF (AFW-VI)***

*PREMIUM SYNTHETIC MULTI-VEHICLE AUTOMATIC TRANSMISSION FLUID*  
Meet or exceed requirements of General Motors' DEXRON®-VI specification.

---

### **DESCRIPTION**

AISIN AFW-VI is formulated with synthetic technology base oil and advanced high-performance additives and meets or exceeds the stringent requirements of General Motors' DEXRON®-VI specification. Aisin AFW-VI also meets the requirements of latest OEM specifications such as Toyota, Hyundai/Kia, MB and VW. It is also suitable for most modern 6+ speed automatic transmissions.

### **CUSTOMER BENEFITS**

- Excellent antifoam performance
- Provides more stable friction property.
- Provides good start operation in cold climates by excellent low-temperature fluidity.
- Oxidation and thermal stability under high temperature conditions
- Provides high shear stability.
- Protect ferrous and non-ferrous materials corrosion

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Aisin, the Aisin logo, and related marks are trademarks of Aisin Asia Pte Ltd, used under license.

Specially formulated fluid designed to meet the requirements of a wide range of Automatic Transmission Specifications: -

### AT FLUID WIDE RANGE MEET GM DEXRON-VI (AFW-VI)

| AUTOMAKER           | SPECIFIED GENUINE ATF   |
|---------------------|---|
| GENERAL MOTORS (GM) | GM: DEXRON®-VI  |
| Audi                | 5 HP LT71141, G 052 162-A1/A2   |
| BMW/Mini            | ATF 3+, JWS 3309 (T-IV), LA2634, ZF 5HP18FL, 5HP24, 5HP30                 |
| Chrysler/Dodge/Jeep | ATF+, +2, +3, +4, AS68RC ATF, MB 236.12                                   |
| MERCEDES BENZ       | MB 236.10, MB236.11, MB236.12, MB236.14                                   |
| Jaguar              | ATF 3403 M115, LT71141, ZF 5HP24, JLM 20292, JLM 21044, WSS-M2C9220-A1    |
| Porsche             | ZF 5HP19FL, ZF 5HP20, LT71141, ATF 3403-M115, T-IV (JWS 3309)             |
| Renault             | Matic D2  |
| Volkswagen (VW)     | 5HP (ZF 5HP 30), 5HP (18FL, 30), 5HP (19FL, 24A), TL 521 62, G 052 025 A2 |

**\*Not for use in CVT applications**

### KEY PROPERTIES

| Synthetic          | Density, kg/liter<br>@ 15°C | Kinematic Viscosity,<br>mm <sup>2</sup> /s |         | Pour Point<br>(°C) | Flash Point<br>(°C) | Brookfield<br>Viscosity<br>mPa·s @ -20°C | Brookfield<br>Viscosity<br>mPa·s @ -40°C |
|--------------------|-----------------------------|--|---------|--------------------|---------------------|--|--|
|                    |                             | @ 40°C                                     | @ 100°C |                    |                     |  |  |
| Fully<br>Synthetic | 0.8463                      | <b>30.86</b>                               | 6.12    | -48                | 220                 | 864                                      | 12,125                                   |

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Aisin, the Aisin logo, and related marks are trademarks of Aisin Asia Pte Ltd, used under license.